

What is claimed is:

1. A portable radiation imaging system comprising:

a radiation source; and

5 a two dimensional radiation image detection device that records a radiation image by detecting the radiation emitted from said radiation source and is transmitted through a subject; wherein both said elements are structured to be carriable, further comprising:

10 an angular signal output means that outputs an angular signal which represents the degree of tilt of the radiation emitted from said radiation source in relation to the detection surface of said radiation image detection device; and

15 a tilt adjustment means that adjusts said tilt of the radiation in relation to the detection surface of the radiation image detection device to become substantially perpendicular by changing the tilt angle of said radiation source based on said angular signal output from said angular signal output means.

2. A portable radiation imaging system comprising:

a radiation source; and

20 a two dimensional radiation image detection device that records a radiation image by detecting the radiation emitted from said radiation source and is transmitted through a subject; wherein both said elements are structured to be carriable, further comprising:

25 an angular signal output means that outputs an angular signal which represents the degree of tilt of the radiation

emitted from said radiation source in relation to the detection surface of said radiation image detection device; and

5 a tilt adjustment means that adjusts said tilt of the radiation in relation to the detection surface of the radiation image detection device to become substantially perpendicular by changing the tilt angle of said radiation image detection device based on said angular signal output from said angular signal output means.

3. A portable radiation imaging system comprising:

10 a radiation source; and

a two dimensional radiation image detection device that records a radiation image by detecting the radiation emitted from said radiation source and is transmitted through a subject; wherein both said elements are structured to be carriable,  
15 further comprising:

a command means that generates an exposure command to said radiation source when the tilt of the radiation to be emitted from said radiation source in relation to the detection surface of said radiation image detection device is substantially  
20 perpendicular.

4. A radiation imaging system according to any one of claim 1, 2, or 3, further comprising a portable shift means that enables horizontal movement of the radiation source.

5. A radiation imaging system according to any one of  
25 claim 1, 2, or 3, further comprising a portable shift means that enables horizontal movement of the radiation image

detection device.

6. A two dimensional radiation image detection device capable of recording a radiation image equipped with an angular signal output means that outputs an angular signal which  
5 represents the degree of tilt of the radiation emitted from a radiation source in relation to the detection surface of said radiation image detection device.

7. A two dimensional radiation image detection device capable of recording a radiation image equipped with a command  
10 means that generates an exposure command to the radiation source when the tilt of the radiation to be emitted by a radiation source in relation to the detection surface of said radiation image detection device is substantially perpendicular.

Add  
A2